





# **Superior Data Capture and Visibility Boosts All-day Workflow Efficiency**



CipherLab's RS36, the successor to the RS35, is a durable, enterprise-class touch mobile computer featuring new scan engine options and enhanced functionality. Operating on Android 12 or Android 14, with future support to Android 14/16, it offers exceptional versatility and simplicity, reducing onboarding time and boosting productivity.

### **Reliable Data Access and Communication** for Frontline Workers

With advanced scanning capabilities, powerful processing, and an intuitive touchscreen, the RS36 ensures secure, reliable data connections and is built for rugged, off-site use. It also integrates seamlessly with CipherLab's mobile device management software, enabling efficient deployment and management. These features empower mobile workforces to achieve more in less time.





#### Flexible Data Capture with Agile **Performance**

The RS36 supports 1D/2D barcode scanning, HF RFID, and NFC, with both standard and extended range options. It can be integrated with a UHF RFID reader to capture over 900 tags per second at 8+ meters. For short-range needs, the RS36 NUHF RFID reader handles 100 tags per second at up to 5 meters, enhancing inventory and asset tracking efficiency.



### **Seamless Connection Inside and Outside Your Facilities**

Mobile workers need timely access to information. The RS36 provides seamless Wi-Fi, Bluetooth 5.1, and Wi-Fi 6 for fast, reliable connections. Its 2x2 MU-MIMO tech ensures low latency in crowded environments, while 4G LTE keeps field workers connected to crucial data anywhere.



## **Rugged Design Protection and Sunlight Readable Display**

The RS36 features a 5.5" screen with 630 nits brightness, supporting gloves or stylus use. Its rugged design withstands 1.5-meter drops (1.8 meters with rubber boot) onto concrete. With IP65/IP68 water and dust resistance, it's reliable in tough environments, including rainy conditions. It also has Corning Gorilla Glass and a wide operating temperature range.



## **Fast Capture High-Res Photos With PDAF** and Recognize Characters With OCR

The RS36's 16MP PDAF rear camera captures sharp images quickly, even in low light or motion, ideal for proof of delivery and condition checks. The 5MP front camera enables video communication for enhanced service. Its OCR capability allows reading characters like serial numbers and expiration dates, streamlining tasks and reducing typing errors in warehousing and delivery.

## **Dependable Performance for Demanding Operations**



The RS36's Qualcomm octa-core 2GHz CPU offers exceptional speed, enhanced app performance, and lower battery consumption. It supports smoother applications and web browsing, and is Android Enterprise Recommended (AER) and Google Mobile Services (GMS) verified. With 4GB/64GB memory, it handles data efficiently. The device features 4000 mAh or 6000 mAh batteries and a hot-swap function for seamless battery replacement.

## **Maximize Your CipherLab Gear to Make It a Total Solution**



## ReMoCloud

ReMoCloud is mobile device management software developed by CipherLab to efficiently manage remote devices over the internet. Administrators can use this to gain visibility into employee devices.



#### EnDeCloud

CipherLab's deployment tool provides mobile computer administrators with different options to manage configurations efficiently and according to their needs.



#### Management Tools

CipherLab's full-featured and enterprise-oriented tools help IT technicians or SI develop mobile device configuration projects for various needs.



## Operation Tools

These tools enable field workers to work seamlessly and efficiently in a userfriendly Android interface.

# An Enterprise Tool that Maximizes Work Efficiency Indoors and Outdoors



Slim and compact design







Supports Wi-Fi 6, 2x2 MU-MIMO, and Bluetooth 5.1





Easily add UHF RFID reading capability by attaching RS36 onto its UHF RFID reader.



android

Android 12 operating system, GMS certificated





OCR recognizes numbers and characters printed on items.



16MP PDAF rear camera with LED flash



Quick-release hand strap saves time in battery replacement



1D/2D barcode data capture.
NFC and HF RFID capability.







5.5" touch display provides a larger work surface and increases visibility







Sunlight readable



One-piece battery



Hot-swap function

Allows the device to stay operational during the battery replacement



Touch panel welcomes input from stylus and fingers (bare, wet, and gloved)









IP68





Andraid 12 or 14 (CMC) Unavadaghla to Andraid 14 / 14











Performance	Operating System	Android 12 or 14 (GMS), Upgradeable to Android 14 / 16	
	CPU	Qualcomm Octa-core 2GHz	
	Memory	64GB UFS Flash / 4GB LPDDR4X RAM	
	Expansion	Micro SD card slot with SDHC (up to 32GB) and SDXC (up to 2TB) support	
	SIM	2 nano SIM/ 1 nano SIM and 1 eSIM (optional)	
	Operating Power	Hot-swappable and rechargeable 3.85V, Li-ion 4000mAh , Extended battery: 6000mAh	
	Working Hours <sup>1</sup>	12+ hours (standard battery), 18+ hours (extended battery)	
	Alert	1 tri-color LED, 1 bi-color LED, vibrator	
	Interface Supported	6-pin I/O & USB 3.1 Gen 1 Type-C with OTG	
Wireless Communication	WWAN	EDGE/GPRS/GSM: 850/900/1800/1900 UMTS/HSPA+: B1/B2/B4/ B5/B6/B8 FDD LTE: B1/B2/B3/B4/B5/B7/B8/B12/B13/ B1/B1/B1/B20/B25/B26/B28/B66 TDD-LTE: B38/39/40/41 Support VoLTE and Worldwide Band	
	WLAN	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w, IEEE 802.11ax (WI-FI 6 model only)	
	Additional WLAN Features	802.11r (fast roaming), 802.11 v/k (Voice-Enterprise), MU-MIMO 2x2 (Wi-Fi 6 model only)	
	WPAN	Bluetooth® Class II, V5.1 dual mode, V2.1 with Enhanced Data Rate (EDR)	
	GPS <sup>3</sup>	GPS/A-GPS/GLONASS/Galileo/Beidou	
Data Capture	Barcode Scanning	1D/2D imager (Standard range: SE4100/SE4770; Advanced range SE5500)	
	RFID Read / Write	HF RFID 13.56 MHz frequency which supports ISO14443A, ISO14443B, ISO15693, and Felica Support NFC (Peer-to-Peer, Card Reader, Card Emulation)	
	Camera	Rear :16 megapixels PDAF with LED flash / Front:5 megapixels <sup>2</sup>	
Physical Characteristics	Display	5.5" HD+ 720 (W) x 1440 (H), Transmissive IPS LCD, outdoor visibility (630 nit), optically bonded Touch Panel	
	Touch Panel	Corning® Gorilla® Cover Glass, Capacitive touch supports stylus, bare or gloved fingertip input multi-touch, allow water rejection and wet finger	
	Interactive Sensor Technology	Light sensor, Proximity sensor, Motion sensor (Accelerometer, G-sensor), E-compass (Magnetometer), Gyroscope	
	Keypad	1 programmable key, volume up and down keys, left and right trigger keys, power key	
	Audio	Speaker (80 dB at 40 cm), microphones with echo and noise cancellation	
	Size (LxWxH)	165 x 76.8 x 17.9 mm	
	Weight	288g (with 4000mAh battery) / 319g (with 6000mAh battery)	
User Environment	Operating Temperature <sup>4</sup>	-20°C to 50°C / -4°F to 122°F	
	Storage Temperature	-30°C to 70°C / -22°F to 158°F (without battery)	
	Humidity (non-condensed)	Operating 10% to 90% / Storage 5% to 95%	
	Impact Resistance	IP65 & IP68  With extended battery: 1.5m multiple drops (36 times), 500 tumbles.  With standard battery: 1.5m multiple drops (36 times) & MIL-810H multiple drops (26 times), 1500 tumbles.  With rubber boot: 1.8m (6 ft.) multiple drops onto concrete, 6 drops on each side.	
	Electrostatic Discharge	± 15 kV air discharge, ± 8 kV contact discharge	
	Regularity Compliance	LTE : CE, FCC, IC, NCC, TBL, JRL, BIS, WPC, WEEE, RoHS, REACH, CA65, TSCA, BC, NrCAN, NBTC WI-FI 6 ONLY : SRRC, CCC, BSMI, NCC, CE, FCC, IC, WEEE, RoHS, REACH, CA65, TSCA, BC, NrCAN	
Development Support	Android 12.0 SDK, HTML 5 API, Reader API (Java/Xamarin)		
Application Software	ReMoCloud, EnDeCloud, ADC, WMDS, APPLock, Terminal Emulator, BT Printer Mate, Device Health, SIP Controller, Software Trigger, Signature Capture, EZEdit, CipherLab Assistant Service, Ping Tool, Wireless Initiator, IntelliWorker, Reader Config, Button Assignment, HF RFID Config, EZConfig, Enterprise Setting, Barcode To Setting, LogGen, Agility Intelligence, Cloud Message, EZcheck		
Certified Application	ReMoCloud, EnDeCloud, SOTI MobiControl, VMware Workspace ONE, Ivanti Wavelink Velocity		
Accessories	Charging and communication cradle, USB snap-on cable, Hand strap, Rubber boot, Pistol grip,4-slot battery charger, Multi-slot Terminal charging cradle², UHF RFID reader², Screen protector²		
Warranty	1 year standard warranty		

1. Minimum hours under WLAN and 2D scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a/b/g/n/ac on. The test is based on one broadcasting packet per second.

**ACCESSORIES** 

1. Minimum hours under WLAN and 2D scanning per 2D seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth\* off / Bluetooth







4-Slot Battery Charger



Charging and Communication Cradle



Snap-on Cable



Rubber Boot



Hand Strap





UHF RFID Reader (work with standard battery only)



Pistol Grip (work with standard battery only)



5-Slot Terminal Charging Cradle



Battery Charger with Terminal Charging Cradle



Extended Battery



Headquarters CipherLab Co., Ltd. 12F, No. 333, Sec. 2, Dunhua S. Rd., Da'an Dist., Taipei City 106033, Taiwan Tel: +886 2 8647 1166 Fax: +886 2 8732 3300

CipherLab China

3115 Room, No.317 Xianxia Road, Changning District, Shanghai, China 200050 Tel: +86 21 3368 0288 Toll Free: +86 400 920 0285 Fax: +86 21 3368 0286 2552 Summit Ave. STE 400 Plano, Texas 75074, USA

CipherLab USA

Tel: +1 469 241 9779 Toll Free: +1 888 300 9779 Fax: +1 469 241 0697

Cahorslaan 24, 5627 BX Eindhoven, The Netherlands CipherLab Europe Tel: +31 (0) 40 2990202